

BOOK OF THE MONTH

5 More specifically, the present invention describes a route optimization technique requiring no awareness of the mobile IP protocol by a Correspondent Node. Still the invention makes it possible to forward traffic using the shortest path between a Mobile Node and the Correspondent Node in a visiting domain.

IP: Internet Protocol. IP is a network layer protocol according to the ISO protocol layering. IP is the major end-to-end protocol between Mobile and Fixed End-

This mobility addressing dilemma is handled in mobile IP by allowing the mobile node to be associated with two IP addresses: a static, “home” address and a

5

10

20

Foreign agents regularly broadcast agent advertisements that include information about one or more care-of addresses. When a mobile node receives an

5

10

15

20

30

the tunneling node has an out-of-date binding cache entry for this mobile node. In this case, the receiving node should send a binding warning message to the mobile node's home agent, advising it to send a binding update message to the node that tunneled this datagram. The mobile node's home agent can be determined from the binding cache entry, because the home agent address is learned from the binding update (that established the cache entry in the first place.) The address of the node that tunneled this datagram can be determined from the datagram's header, since the address of the node tunneling this IP datagram is the outer source address of the encapsulated datagram. As in the case of a binding update sent by the mobile node's home agent, no acknowledgment of this binding warning is needed, since additional future datagrams for the mobile node tunneled by the same node will cause the transmission of another binding warning.

As part of the registration procedure, the mobile node may request that its new foreign agent attempts to notify its previous foreign agent, by including a previous foreign agent notification extension in its registration request message sent to the new foreign agent. The new foreign agent then builds a binding update message and transmits it to the mobile node's previous foreign agent as part of the registration. The new foreign agent requests an acknowledgment of the binding update from the previous foreign agent. This extension includes only those values needed to construct the binding update message that are not already contained in the registration request message. The authenticator for the binding update message is computed by the mobile node using the security association shared with its previous foreign agent. This notification will typically include the mobile node's new care-of address, allowing the previous foreign agent to create a binding cache entry for the mobile node to serve as a forwarding pointer to its new location. Any tunneled datagrams for the mobile node, that arrive at its previous foreign agent after the forwarding pointer has been created, can then be re-tunneled to the mobile node's new care-of address.

The present invention aims at providing a similar result in the form of route optimization, while not requiring the correspondent node to be aware of the mobile IP protocol. In addition to the above mentioned route optimization draft, the following references are also of general interest for the understanding of the present invention:

Alexander, S. et al; DHCP Options and BOOTP Vendor Extensions;
<http://www.ietf.org/rfc/rfc2132.txt>; March 1997.

Calhoun, Pat et al; DIAMETER Base Protocol; <http://www.ietf.org/internet-drafts/draft-calhoun-diameter-17.txt> and <http://www.diameter.org/>; September 2000

5 Calhoun, Pat et al; DIAMETER Mobile IP Extensions;
<http://www.ietf.org/internet-drafts/draft-calhoun-diameter-mobileip-11.txt>; September 2000.

Calhoun, Pat et al; Mobile IP Network Access Identifier Extension for IPv4;
 RFC2794; <http://www.ietf.org/rfc/rfc2002.txt>; March 2000.

10 Dierks, T et al; The TLS Protocol, First Version; RFC2246;
<http://www.ietf.org/rfc/rfc2246>; January 1999.

Droms, R.; Dynamic Host Configuration Protocol; RFC2131;
<http://www.ietf.org/rfc/rfc2131.txt>; March 1997.

Knight, S et al; Virtual Router Redundancy Protocol; RFC2338;
 15 <ftp://ftp.isi.edu/in-notes/rfc2338.txt>; April 1998.

Montenegro, G.; Reverse Tunneling for Mobile IP; RFC2344;
<http://www.ietf.org/rfc/rfc2344.txt>; May 1998.

Perkins, Charlie; IP Mobility Support; RFC2002;
<http://www.ietf.org/rfc/rfc2002.txt>; October 1996.

20 **Summary of invention**

The present invention describes a route optimization technique requiring no awareness of the mobile IP protocol by a correspondent node when forwarding traffic using the shortest path between a mobile node and the correspondent node in a visiting domain. The invention describes the management of route entries, network address translations and firewall filters in order to provide a secure, yet, flexible deployment of mobile IP route optimization. Specific considerations are described for the case of separate/standalone foreign agent and co-located care-of address respectively.

30 Fig. 3a illustrates the traffic flow between the mobile node 3 and the correspondent nodes CN 4 when applying above mentioned route optimization. The traffic between the mobile node 3 and the correspondent node CN 4a, i.e. the host situated on the home network 9, will be routed through the mobile IP tunnel 30a over

the logical interface 32a by the foreign agent 2. Similarly, the datagrams sent from/to the correspondent node CN 4d on the Internet are tunneled to the home agent 1. The reason for the latter is that the home agent 1 then can advertise an aggregate route for the whole home network 9 towards the Internet instead of advertising mobile node 3 specific routes from individual foreign agents 2.

On the other hand, traffic sent from/to the correspondent nodes 4b and 4c at the local site, hosted by router 5a, are sent the shortest path directly out on one of the local interfaces 32b and 32c of the foreign agent 2 instead of being tunneled to the home agent 1. This is done by setting a static route in the foreign agent 2, which favors a direct route to the visited subnetwork 8 from the mobile node 3 for traffic from the correspondent node 4b and 4c. Similarly, a static route for traffic from the mobile node 3 to the correspondent node 4b and 4c is established in order to send traffic directly out on the interface 32b and 32c.

Brief description of the drawings

The foregoing and other objects, features, and advantages of the invention will be apparent from the following description of preferred example embodiments as well as illustrated in the accompanying drawings in which:

Fig. 1 is a function block diagram illustrating the components in mobile IP when using a separate foreign agent,

Fig. 2 is a function block diagram illustrating the components within the foreign agent as applied in the present invention,

Fig. 3a is a flow chart diagram illustrating the route optimization technique in case of a separate foreign agent,

Fig. 3b is a flow chart diagram illustrating handover between foreign agents,

Fig. 3c is a flow chart diagram illustrating the route optimization in foreign agent in case of overlapping address realms,

Fig. 4 is a function block diagram illustrating the mobile filter state table in the foreign agent as applied in the present invention,

Fig. 5 is a function block diagram illustrating the routing table of the foreign agent when having the mobile node attached,

- Fig. 6a is a flow chart diagram illustrating the static route and filter distribution as part of the mobile IP registration procedure when using a separate foreign agent,
- Fig. 6b is a diagram illustrating the mobile IP extension format for static route,
- Fig. 6c is a diagram illustrating the mobile IP extension format for firewall filters,
- Fig. 7 is a function block diagram illustrating the components in mobile IP when using a co-located care-of address,
- Fig. 8 is a function block diagram illustrating the components in the mobile node as applied in the present invention,
- Fig. 9a is a flow chart diagram illustrating the route optimization technique in case of a co-located care-of address,
- Fig. 9b is a flow chart diagram illustrating the traversal of a firewall with network address port translation in the case of a co-located care-of address,
- Fig. 10 is a diagram illustrating the mobile firewall state table in the mobile node as applied in the present invention,
- Fig. 11 is a diagram illustrating the routing table of the mobile node when attached to a visited subnetwork,
- Fig. 12a is a flow chart diagram illustrating the static route and filter distribution at mobile IP registration time when using a co-located care-of address,
- Fig. 12b is a flow chart diagram illustrating the registration procedure in case of traversing a network address port translator,
- Fig. 13a is a flow chart diagram illustrating the home agent failover support in the home network using the virtual router redundancy protocol.
- Fig. 13b is a diagram illustrating the format of packet type mobile IP registration dump in the virtual router redundancy protocol,
- Fig. 14a is a function block diagram illustrating the load distribution in the home network using a Load Balancer,
- Fig. 14b is a function block diagram illustrating the configuration of the Load Balancer,

Fig. 15a is flow chart diagram illustrating the distribution of X.509 certificates and establishment of security associations in mobile IP,

Fig. 15b is a diagram illustrating the mobile IP extension format for X509 certificates,

Fig. 15c is a diagram illustrating the format of an X509 certificate, and

Fig. 15d is a flow chart diagram illustrating the usage of transport layer proxy in foreign and home agent respectively.

While individual functional blocks and components are shown in many of the figures, those skilled in the art will appreciate these functions may be performed by software modules or programs executed using a suitably programmed digital microprocessor or general purpose computer by individual hardware circuits, by an application specific integrated circuit (ASIC), and/or by one or more digital signaling processors (DSPs).

Detailed description of preferred embodiments

In the following description, for purposes of explanation and not limitation, specific details are set forth, such as particular embodiments, circuits, signal formats, techniques, etc. in order to provide a thorough understanding of the present invention. Although specific protocols are referred to for purposes of facilitating the description, the present invention is not necessarily limited to such specific protocols. However, it will be apparent to one skilled in the art that the present invention may be practiced in other embodiments that depart from these specific details. In other instances, detailed descriptions of well-known methods, devices, and circuits are omitted so as not to obscure the description of the present invention with unnecessary detail.

The present invention provides a route optimization technique requiring no awareness of the mobile IP protocol by a Correspondent Node when forwarding traffic using the shortest path between a Mobile Node and the Correspondent Node in a visiting domain.

Fig. 1 illustrates the components in mobile IP when standalone foreign agents 2 are deployed outside a home network 9, where the home agent 1 (HA) and

its mobile service manager 7 (MSM) are installed. The base mobile IP protocol allows any mobile node 3 (MN) to move around, changing its point of attachment to the Internet 6, while continuing to be identified by its IP address in the home network 9. Correspondent nodes 4 (CN) send IP datagrams to a mobile node at its home address in the same way it would with any other destination. This scheme allows transparent interoperability between mobile nodes 3 and their correspondent nodes 4, but forces all datagrams for a mobile node 3 to be routed through its home agent 1. Thus, datagrams to the mobile node 3 are often routed along paths that are significantly longer than optimal. For example, if a mobile node 3 is visiting some visited network 8, even datagrams from a correspondent node 4b on the same subnet must be routed through the Internet 6 to the mobile node's 3 home agent 1 (on its home network 9), only then to be tunneled back to the original visited subnetwork 8 and its foreign agent 2 (acting as router) for final delivery. This "indirect routing" delays the delivery of the datagrams to mobile nodes 3, and places an unnecessary burden on the networks and routers along their paths through the Internet 6.

This invention defines extensions to the operation of the base mobile IP protocol to allow for better routing, so that datagrams can be routed from a correspondent node 4 to a mobile node 3 without going to the home agent 2 first. We refer collectively to these extensions as Route Optimization. In contrast to earlier methods for route optimization, the following invention does not enforce any requirements on mobile IP protocol awareness on the correspondent node 4.

Fig. 2 illustrates the components available in the foreign agent 2. The foreign agent 2 has an LDAP (Lightweight Directory Access Protocol) interface towards the management network 10. One specific entity on the management network 10 is the mobile service manager (MSM) 7, which provides the foreign agent 2 with among other things its own certificate signed by the MSM 7, its private key and the MSM 7 certificate. Note that the private key is not necessarily distributed using the LDAP protocol, but rather may constitute a hardware token or be configured locally at the command line interface of the foreign agent 2. An even more general solution is to require the mobile IP 27 entity to generate its own private and public key and submit the public key to the mobile service manager 7 for certificate creation and signing. This alternative avoids the private key to ever leave the mobile IP 27 entity and, thus

In addition, the MSM 7 may configure the foreign agent 2 with firewall filters and static routes for mobile nodes 3 located on the visited network 8. However, as is explained in fig. 6a, this invention also provides a dynamic mechanism for distributing such information from the home agent 1 during the mobile IP 27 and DIAMETER 26 registration procedure. Authenticity and Integrity of those registration extensions are provided by the mobile IP 27 authenticator, which in turn allows the home agent 1 and foreign agent 2 to communicate over the Internet 6.

The mobile firewall 18 is a new component in a foreign agent 2 compared to the mobile IP standard, IETF RFC 2002. The mobile firewall 18 receives a set of firewall filter definitions from the mobile IP control engine 16 as part of the registration procedure. The received filters are applied to traffic from/towards the mobile node 3 during the time that the mobile node 3 has a valid registration with the home agent 1.

Fig. 3a illustrates the traffic flow between the mobile node 3 and the correspondent nodes CN 4 when applying route optimization. The traffic between the

5

10

20

30

Several scenarios have to be considered. For example, the home network 9 address realms for visiting mobile nodes 3 and 3b may be overlapping. For this purpose, the mobile firewall 18 of the foreign agent 2a includes a network address translation (NAT) 34a function indexed by mobile node 3 IP address and link layer address 53.

Another case of overlapping IP address realms occurs when the mobile node 3 is entering a visited subnetwork 8 in which the foreign agent 2a has received address information via the address resolution protocol (ARP) or a routing protocol that indicates overlap with the home network 9 routes or even the mobile node 3 IP address. In the first case, the foreign agent will merely route the traffic through the MIP tunnel 30a and ignore the local correspondent node with the overlapping address CN 4e. In the latter case, a NAT 34b in the mobile firewall 18 of the foreign agent 2 has the task of giving a temporary IP address to the mobile node 3 for traffic towards correspondent node CN 4c. This NAT 34b solution will not survive a movement of a mobile node 3 to another foreign agent 2b. The reason is that the mobile node 3 is using a temporary IP address, hosted by the first foreign agent 2a, in its communication with the correspondent node CN 4c.

- Source IP address 40;
- Destination IP address 41;

- Protocol Type 50;
- Network address translation (NAT) index 51; and
- Action 52.

For the traffic coming through the mobile IP tunnel 30a, the filter state table 22 is not applying any NAT index 51. The traffic is filtered based on protocol type 50. Any 50a type of protocol is accepted 58 to be sent between the mobile node 3 and the correspondent node 4a. Session Invitation Protocol (SIP) and Real-time Transport Protocol (RTP) 50d are explicitly denied 56 to be sent between the mobile node 3 and the correspondent node 4d. For the HTTP 50b traffic from the mobile node 3 to the correspondent node 4b, the foreign agent 2a applies a dynamic NAT index 51 based on the mobile node IP address 3 and MAC address 53 in order to separate traffic destined for mobile node 3 and 3b. The NAT is stateful 54, meaning that HTTP 50b traffic sent from the correspondent node 4b to the mobile node 3 is reverse NAT based on the session-id allocated at the outgoing HTTP 50b traffic case. Similarly, traffic from the mobile node 3 to the correspondent node 4c will be allocated a NAT index 51. In this case the foreign agent 2a will allocate a temporary new IP address to the mobile node 3 in order to not collide with the address of correspondent node 4c. Any 50a traffic is accepted 58. It is also mandated by the action column 52 that the data is to be logged 59.

Fig. 5 shows the corresponding routing table 24 of the foreign agent 2a. The routing table 24 has four columns:

- Source IP address 40;
- Destination IP address 41;
- Nexthop 42; and
- Routing Cost 43.

The routing of traffic from the mobile node 3 to the different correspondent node 4 is based on static routes received during the registration procedure from the home agent 1 (see fig. 6 for more details). The routes are source-restricted as they only apply to the mobile node 3. As can be seen from the nexthop column 42, the tunnel interface 32a is favored for traffic towards correspondent node 4a and 4d, while the foreign agent 2a local interfaces 32b and 32c are used for datagrams towards the correspondent nodes 4b and 4c respectively. More specifically, route decisions are based on routing costs 43 in case multiple route entries exist for the

same destination. The routing cost is set by routing policies 44-47 (RP). The routing table 24 includes multiple routes for the IP addresses of correspondent node 4a and 4d respectively. The routing policy 44a has lower cost than 44b for the purpose of favoring the correspondent node 4a in favor of 4e at address collisions between the home network 9 and visited network 8b. Furthermore, the routing policy 45a has lower cost than 45b in order to ensure a proper reverse path towards the correspondent node 4d. A more complicated situation occurs in case a correspondent node 4c has the same address as the mobile node 3. In the case of overlapping IP address realms, the mobile node 3 must be instructed to send traffic towards the foreign agent 2a even if the destination IP address is the same as the mobile node source IP address 3. This was the case with correspondent node 4c. Similarly, the foreign agent 2a is required to allocate a higher cost (48b) for the route having nexthop equal to the mobile node 3, i.e. interface 32b, than the cost (48a) given to routes having the same destination IP address but learned from nexthops other than the mobile node 3, in this case interface 32c. Strictly speaking, the foreign agent 2a will favor other destinations than the mobile node 3 in case it gets a datagram with source address equal to the destination address from the mobile node 3. A network address translation will be applied to the mobile node 3 source address, as described in fig. 5, before being sent out on the visited network 8a.

When it comes to routes for reaching the mobile node 3, the interface 32b is favored regardless if datagrams comes via the mobile IP tunnel 30a or directly on a local interface 32b or 32c. However, ignoring the problems involved due to overlapping address realms and network address translation, there may be alternative routes published, which makes it important that the routing cost 43 is set correctly. An alternate route for reaching the mobile node 3 in the case of correspondent nodes 4b and 4c would be to reach the mobile IP tunnel 30a and interface 33a by going through the Internet 6 back to the home network 9 where the home agent 1 is also advertising a route for the mobile node 3. The routing policy 46a and 47a related to the direct route must always be given lower cost than the route policies 46b and 47b associated with the home agent 1 route. Note that by applying no visibility of the mobile node 3 from the foreign agent 2a towards the Internet 6 ensures that the home network 9 is published as an aggregate route towards the Internet 6, i.e. no individual routes are published directly from the visited

Fig. 6a shows the mobile IP registration procedure when a standalone foreign agent 2 is available at the visited subnetwork 8. Of specific interest to this invention is the distribution of mobile node filters 60 and static routes 61 to be used in the foreign agent 2 filter state table 22 and routing table 24 respectively. In the management plane 150, the home agent 1 is retrieving mobile node filters 60 and static routes 61 using the lightweight directory access protocol (LDAP) 25. In the control plane 151, the home agent 1 will add extensions to the mobile IP registration reply for filters 60 and static routes 61 respectively. The foreign agent 2 will strip the mobile IP registration reply from these extensions before passing it on to the mobile node 3. It will then use the filters 60 and static routes 61 as described in Fig 4 and 5 in order to route and filter the payload 152 i.e. IP packets to/from the mobile node 3.

- Type 62: NVSE-Type-Number (to be assigned by IANA);
- Length 63: Length in bytes of this extension, not including the Type and Length field;
- Reserved 66: Reserved for future use. To be set to 0;
- Vendor/Org-ID 64: The high order octet is set to 0, the low order 3 octets are the SMI Network Management Private Enterprise Code of the Vendor in network byte order as defined in the Assigned Numbers RFC;
- Vendor-NVSE-Type 65: Indicates the particular type for the Vendor-NVSE-Extension. In this case it indicates Static Routes; and
- Vendor-NVSE-Value 61: In this case Static Route, two IP addresses (Static Route) where the first one is the destination address and the second is the router for that address. The number of static routes may be computed from the Length field value.

Fig. 6c shows the corresponding extension in mobile IP 27 for the purpose of distributing firewall filters 60 from the home agent 1 to the foreign agent 2 as part of the registration reply message. The fields have the same meaning as described in

Fig. 6b except for the last two items:

- Vendor-NVSE-Type 65: Indicates the particular type for the Vendor-NVSE-Extension. In this case it indicates Filter Rules; and
- Vendor-NVSE-Value 60: In this case Filter Rules. Each filter rule contains a source IP address, a destination IP address, a protocol descriptor and an action. The number of Filter Rules may be computed from the Length field value.

Fig. 7 shows the basic configuration for mobile IP 27 in case no foreign agent 2 is available at the visited network 8. The case is denoted co-located Care-of Address 100 and is of specific interest as a remote access solution to the home network 9 from anywhere on the Internet 6.

When the mobile node 3 is entering the visited subnetwork 8, and cannot find a foreign agent 3, it will request a care-of address 100 using the dynamic host configuration protocol (DHCP) 72 towards the local router 5c. When having received a care-of address 100, the mobile node 3 will start its mobile IP 27 registration procedure with the home agent. According to the mobile IP standard RFC 2002, the mobile node 3 will then use a mobile IP tunnel 30a for all traffic going from and to it. As was discussed in Fig. 1, in the case of a standalone/separate foreign agent 3, the compulsory tunneling of datagrams to the home agent 1 causes them to take a longer path than if a direct route to local resources was available. In Fig. 7 traffic between the mobile node 3 and the correspondent nodes 4b and 4c would benefit from such direct routing.

Fig. 8 illustrates the components of a mobile node 3 in which optimized routing is possible both for the case of standalone/separate foreign agent 2 and co-located care of address 100. This is exemplified by four virtual interface adapters 85 running on top of two physical network interface cards for local area network 88a and wireless local area network 88b.

- A virtual interface adapter 85a using a co-located care-of address 100 for direct traffic on the visited network 8;
- A virtual interface adapter 85b using a standalone foreign agent 2 for reverse tunneled traffic from/to the home network 9;
- A virtual interface adapter 85c using a standalone foreign agent 2 for direct traffic on the visited network 8; and

- Note that the combinations 85a/85d and 85b/85c are mutually exclusive, i.e. they will not be active at the same time.

In between the physical and virtual interfaces is a network interface card selection module 87 that takes decision about which physical interface to run over at each point in time by maximizing availability and bandwidth for the mobile IP 27 payload 152. In addition, the mobile IP 27 control engine 86 is situated at this level in the mobile node's 3 protocol stack. The mobile IP 27 control engine 86 interacts with most other modules in the stack. In the initialization phase of a physical interface 88, it retrieves the IP address that will be used as the care-of address 100 from the DHCP client 82. It sends a mobile IP 27 registration message to the selected network interface card 88 and configures them together with the virtual interface adapters with care-of IP address 100, foreign agent 2 IP address, home agent 1 IP address, tunnel type (IP-IP, GRE or minimal IP), etc. It dispatches information to the mobile firewall 83b, Internet key exchange 80 and TCP/IP routing table 81 about filters, IPSec routes and peers and route costs respectively. The Internet key exchange 80 instructs the IPSec filter 84a via the security association database 84d to utilize security associations with, among others, the home agent 1 for traffic sent on the reverse tunneled virtual interface adapters 85b and 85d. Similarly, security associations may be established with the foreign agent 2 for traffic over the virtual interface adapter 85c and maybe directly towards the correspondent node 4 in case of virtual interface adapter 85a.

Several aspects are worth noting in this mobile node 3 architecture.

25 Foremost the architecture allows traffic to be sent via the virtual interface adapters as well as directly to/from the physical network interface cards 88. The decision to encrypt or not is taken per interface and route. Furthermore, the source IP address of each virtual interface adapter 85 is kept stable for the higher layer components, i.e. TCP/IP routing table 81 and firewall filter state table 83a and IPSec filter 84a. This is especially important for the IPSec filter 84a, which requires a stable source IP address. The source IP address for each virtual interface will be:

- 85a: local IP address retrieved by DHCP client 82;
- 85b: stable home address of mobile node 3;

- 85c: stable home address of mobile node 3; and
- 85d: stable home address of mobile node 3.

As a consequence, the application programming interface 89 of the mobile node 3 protocol stack can provide the widest selection of routes possible to a destination based on all physical and virtual interfaces available at each single point in time.

Fig. 9a illustrates the case when optimized routing is applied in a mobile IP 27 co-located care-of address scenario. The entities involved are the same as in the previous scenario shown in fig. 7. However, the mobile node 3 has two interfaces:

- 10 ▪ One interface 90a with the source IP address set as the mobile node 3 IP address 3' for sending and receiving traffic to the home agent 1 via a mobile IP tunnel 30a; and
- One interface 90b with the source IP address set to the care-of address 100 received from the DHCP server 72 and to be used for sending and receiving traffic on the visited network 8.

Datagrams sent between the mobile node 3 and the correspondent nodes 4a and 4d will be sent via the interface 90a, while datagrams sent between the mobile node 3 and the correspondent nodes 4b and 4c will be sent through the local interface 90b. Note that mobility is not achieved for TCP sessions in the latter case as the temporary care-of address is used as the source IP address and the mobile node 3 will be allocated a new care-of address by each foreign agent 2. This may not be a large problem as most of the local applications available at the visited network 8, may only be relevant as long as the mobile node 3 is on the visited network 8, i.e. they will anyway be terminated before leaving the visited network 8. A more advanced solution is to decide which interface 90a or 90b to use for a route based on the port number. In this way applications that are sensitive to source IP address changes, and likely to be used while changing from one foreign agent 2 to another, would be forced to be sent on the interface 90a back to the home agent 1 and in such way survive when a mobile node 3 changes its point of attachment. A typical example of such an application is the session invitation protocol (SIP) and real-time transport protocol (RTP) 50d, which will typically be used for voice over IP calls and e.g. streaming video.

Fig. 9b shows the more complicated scenario where the mobile node 3 is

5

10

15

30

the mobile node address 3 (10.0.0.1) as its source address visible for the applications. Left are four columns in the filter state table 83a, namely the source address 40, the destination address 41, the protocol 50 and the action 52. The filters entries have the same meaning as in fig. 4 and are not repeated here.

The TCP/IP routing table 81 in fig. 11 is less obvious and requires more explanation. The mobile node 3 routing table 81 has the same columns as the foreign agent 2 routing table 24 in fig. 5, i.e. source address 40, destination address 41, nexthop 42 and routing cost 43. In fig. 5 the routing cost 43 is compared for the interface 90a and 90b respectively. 90a is the interface provided by the virtual interface adapter 85d, i.e. leading to the mobile IP tunnel 30, and 90b is the interface provided by the virtual interface adapter 85a, i.e. sending IP traffic directly on the visited subnetwork 8. Note that in a real implementation, also other interfaces in the mobile node 3 may publish routes that have to be taken into account when deciding which interface to send traffic out on. One particular example of this are the physical network interface cards 88a and 88b, which may also make routes available to the routing table 81. In this example it is assumed that the virtual interface adapter 85a always makes its routing cost lower than the physical interface 88 for all routes that are common for the two.

It is possible to reach the destination 10.0.4.3 both through the mobile IP tunnel 30a (interface 90a) and on the visited subnetwork 8 (interface 90b). It is not known to the routing table 81 that actually two different correspondent nodes 4a and 4e are hidden behind these two destination routes. A generic rule is applied in the mobile node 3 routing table 81 to favor the mobile IP tunnel 30a instead of local access, i.e. the routing policy for reverse tunneling 110a is given lower cost than the routing policy for native connectivity 110b in case of overlapping address realm.

Row 3 defines the route for the destination 10.0.0.3. In this case this route is only available on the local visited subnetwork 8 using the interface 90b. This is largely due to the private address nature of the home network 9 and the visited network 8. In a pure public scenario, there would also be a route published for the correspondent node 4b via the home agent 1. In this case the home agent 1 interface 90a would have a higher cost than the local interface 90b as the mobile node 3 can detect that the correspondent node 4b is on the visited subnetwork 8 using the address resolution protocol.

The next two rows in the routing table 81 relates to the destination address 10.0.0.1. From fig. 9b it is possible to deduce that both the mobile node 3 and the correspondent node 4c has this IP address. Similar to what was discussed in fig. 5, the mobile node 3 is required to place a higher routing cost 112a for the localhost interface 90c than the routing cost 112b it has for an external destination on the visited network 8, as is the case with correspondent node 4c.

The last two rows relate to destinations on the Internet 6, and in particular correspondent node 4d with IP address 204.34.9.1. It is a corporate policy decision if the local route via interface 90b or the tunneled route via interface 90a shall be preferred. Both will blend into an aggregate route towards the Internet 9. The local route may have a shorter distance to its destination, but only a session across the tunneled route will survive a move. The final policy may involve a decision based on port number, but in this example the tunneled route is given a lower cost 113a than the cost of the local route 113b.

Fig. 12a illustrates the mobile IP 27 registration procedure when a co-located care-of address 100 is allocated to a mobile node 3. Fig. 12a assumes that the home network 9 and visited network 8 are part of the same address realm. Fig. 12b describes the more complicated case, where a network address translation 92 separates the home and the visited networks into two different realms.

During the management phase 150, the home agent 1 will fetch mobile node 3 data, including mobile node filters 60 and static routes 61, from the mobile service manager 7 using the lightweight directory access protocol 25. At registration request 93 from the mobile node virtual interface adapter 120, the home agent 1 will include the filters 60 and static routes 61 as extensions in the registration reply message as part of the control plane 151 procedures. The mobile node virtual interface adapter 120 can then apply the filters 60 and static routes 61 in very much the same way as the foreign agent 2 did in fig. 6a when payload 152 are sent from the mobile node to the correspondent nodes.

- Datagrams towards correspondent node 4a are tunneled to the home agent 1 using the care-of address 100 as source IP address before being delivered natively on the home network 9 with the mobile node 3 as source address.
- Datagrams to the correspondent nodes 4b and 4c sent directly out on the visited network 8 based on the static routes 61 and using the care-of-address

- Datagrams to the correspondent node 4d from the mobile node 3 are restricted by the filter 60 in order not to allow the real-time transport protocol 50d.

Fig. 12b describes the registration procedure when applying NAPT 92 in
between the mobile node 3 and the home agent 1. The mobile node 3 sends a
mobile IP 27 registration request 93 towards the home agent 1. The registration
request 93 includes the care-of address 100 as one field inside the registration
message. The registration request 93 is sent with the UDP destination port equal 434
and the UDP source port set to any chosen port number. The source IP address of
the registration request 93 is set to the care-of address 100 and the destination IP
address is set to the home agent 1 public IP address 204.8.8.2.

When the registration request 93 is traversing the NAPT 92, the source IP address will be modified to the public IP address of the firewall 91, namely 204.68.9.2. In order to distinguish between datagrams sent from different nodes in the visited network 8, e.g. correspondent node 4b and mobile node 3, the NAPT 92 will also hold a state table with the care-of address 100 and the UDP source port number on the inside and a newly allocated UDP source port number on the outside of the firewall 91. The latter UDP source port number is selected so that it is unique among the sessions traversing the NAPT 92 at any point in time.

The home agent 1 will discover the discrepancy between source IP address 204.68.9.2 and care-of address 10.0.0.2 inside the registration request 93 message. In order to verify the sender, the home agent 1 will send a registration reply reject code "failed authentication" and submit a challenge for the mobile node 3 to respond to. The mobile node 3 will interpret the behavior of the home agent 1 in such a way that a new registration is required for it to pass a NAPT 92. The mobile node 3 calculates the response to the challenge using its key and sends the new registration message. The home agent 1 verifies the response to the challenge using the shared key or public key of the mobile node 3. If authenticated successfully the home agent 1 adds the mobile node filter 60 and static routes 61 in the registration reply message and the payload sessions 152 may start.

There are two differences in the way payload 152 transfer is performed when a NAPT 92 is present in the path as shown in fig. 12b. First of all the payload 152 datagrams to be sent through the mobile IP tunnel 30a are required to have a UDP

5

15

20

25

30

5

10

15

- 20

- 25

- 30

- Data (1..n) 212: Content for transfer (in this case active Mobile IP Registration Request)

The VRRP solution in fig. 13a and b provides failover support between two home agents 1a and 1b for the same virtual home agent IP address 136. The most common setup will be that a home agent acts as primary for one virtual home agent IP address 136 and secondary for another. The effect is a redundant setup that will survive failure of anyone of the involved components, in this case home agents 1.

Fig. 14a illustrates a loadbalancing scheme among a large cluster of home agents 1. Its purpose is to spread the load of all mobile node 3a and 3b control messages 151 and corresponding payload 152 in order to achieve a scalable architecture. The distribution is achieved by having mobile IP datagrams routed to a load balancer 130b with UDP in between the two IP payload headers in a similar way as described for NAPT 92 traversal in Fig. 9b. The load balancer 130b is most often an Ethernet switch 130a equipped with a dispatcher function 131. In this case the dispatcher is using the UDP source port number to dispatch datagrams between the home agents 1. Fig. 14b will explain in more detail how this is done.

An important aspect of loadbalancing is that the mobile node 3 shall not need to be aware that it is present. For this reason, the load balancer 130b will host the home agent 1 IP address 136 that all mobile nodes 3a and 3b on the Internet 6 can use for their registration request messages 93. Traffic will be directed from the load balancer 130b to the home agents' 1a and 1c hardware (e.g. MAC) address 135a and 135c based on UDP port number. All home agents 1 on the home network 9 have the same IP address 136, and reply to clients with that single IP address 136, thus avoiding the overhead of NAT re-writing on the way back.

However, each home agent 1a and 1c will also be equipped with at least one unique IP address on the home network 9 or a separate backend network 134, in order to advertise reachability of the mobile node 3a and 3b towards correspondent nodes 4. As in fig. 13a, the mobile node 3 subscription data may be stored in a separate LDAP or RADIUS server 132 in order for the dispatcher 131 to be independent of mobile node 3. The selected home agent 1a or 1c will not retrieve the mobile node 3 subscription data until receiving the registration request 93.

Fig. 14b describes the schema from which the load balancer 130b dispatch datagrams sent from the mobile node 3 to the home agent 1 IP address 136. The

datagram header format in fig. 14b is numbered according as follows:

- 144a: Outer header destination IP address;
- 144b: Outer header source IP address;
- 146a: UDP destination port number;
- 5 ▪ 146b: UDP source port number;
- 147a: Inner header destination IP address;
- 147b: Inner header source IP address; and
- 145: Content in mobile IP 27 registration request message 93.

It is proposed to use a simple UDP dispatcher 131 based on UDP source
 10 port number 146b as the internal mechanism in the load balancer 130b. In contrast
 to, e.g., a more complex scheme based on mobile node 3 IP address 143, the UDP
 dispatcher 131 will not need to understand the mobile IP protocol 27 and open up
 the registration request message 93.

In order for mobile IP 27 payload from the mobile node 3 or the foreign agent
 15 2 to traverse the load balancer 130 it is required to place a UDP header 146 in
 between the two IP headers 144 and 147 for all payload 152, i.e. the same technique
 that was applied to go through a NAPT 92 in fig. 9b. In addition, the source IP header
 of the payload 152 and the mobile IP control message 151 (specifically the
 registration request message 93) has to have the same source port number in order
 20 for both to be dispatched to the same home agent 1a or 1c by the load balancer
 130b. The mobile node 3 and foreign agent 2 can select a random UDP source port
 number value 148 and the load balancer 130 will use the combined information of
 source IP address 144b and source UDP port number 146b to dispatch to packets.

The header for the registration request message 93 will then have the
 25 following values:

- Destination IP address 144a: home agent IP address 136;
- Source IP address 144b: care-of IP address 100;
- UDP destination port number 146a: 434 (indicates mobile IP 27 control
 message);
- 30 ▪ UDP source port number 146b: Randomly selected value 148; and
- Registration request message content 145: among other things the mobile
 node 3 IP address 143.

Similarly, a payload 152 datagram sent from the mobile node 3 or foreign

agent 2 to the home agent 1 will have the following header values:

- Outer Destination IP address 144a: home agent IP address 136;
- Outer Source IP address 144b: care-of IP address 100;
- UDP destination port number 146a: Randomly selected value 149;
- 5 ▪ UDP source port number 146b: Randomly selected value 148 (but same as for registration request message above);
- Inner Destination IP address 147a: correspondent node 4 IP address 142; and
- Inner Source IP address 147b: mobile node 3 IP address 143.

10 The return traffic from the home agent 1 to the mobile node 3 or foreign agent 2 will not be modified by the load balancer 130b. The same applies to advertisements of mobile node availability 150 through the address resolution protocol or a routing protocol like OSPF 28 or BGP 29. In these cases the home agent 1a or 1c will use its unique IP address instead of the shared home agent IP address. Finally, datagrams sent from the correspondent node 4 will also be sent 15 natively with the mobile node 3 IP address 143 as destination and its own address 142 as source, i.e. without going through the UDP dispatcher 131 of the load balancer 130b.

When allowing a foreign agent 2 to perform route optimization on behalf of 20 the home agent 1, it is of importance to have a flexible key distribution mechanism in order to allow authentication between all entities in the mobile IP 27 system. The mobile IP 27 systems today rely on shared authentication keys between the mobile node 3, the home agent 1 and the foreign agent 2 in order to authenticate the control messages 151. This is not a scalable solution when the number of possible foreign 25 agents 2 increases. One solution to this problem is to keep the shared key solution, but to use an AAA client 14 in the foreign agent 2 in order to distribute shared session keys from the home network 9 using the DIAMETER 26 protocol as shown in fig. 2. Fig. 15a proposes an alternative solution based on public keys and X.509 certificates 154. By applying public keys, each mobile IP 27 entity (mobile node 3, 30 foreign agent 2, and home agent 1) is only required to hold three security entries:

- The private key for the mobile IP 27 entity;
- The public key for itself in the form of an X.509 certificate 154 signed by the mobile service manager 7; and

- The X.509 certificate 154 of the mobile service manager.

This should be compared with holding the shared keys of all the mobile IP 27 entities that it should communicate with.

Fig. 15a describes the registration procedure when extended to support X.509 certificate 154 and public keys. Apart from generating the three security entries as described above, the mobile service manager 7 also makes available a list of revoked certificates 153 to all entities in the mobile IP 27 system through LDAP 25 in the management plane 150, as part of an online certificate status protocol RFC 2560, or in the form of DNS Security RFC 2535 SIG records. The mobile service manager 7 acts as the certificate authority for the mobile IP 27 system, and may in turn have its X.509 certificate 154 signed by a higher order certificate authority, like Verisign, in the case that two or more mobile IP 27 systems, with separate administration, are interconnected.

In the control plane 151, the mobile node will append its own X.509 certificate 154a as an extension to the mobile IP 27 registration request 93. The format of this extension is presented in fig. 15b. The receiving entity (in this case the foreign agent 2) will check that the signature of the X.509 certificate 154d is from the mobile service manager 7 and verify that the mobile node 3 is not in the revocation list 153. This latter check can either be based on a local revocation list, an online certificate status protocol request or DNS query. Fig. 15a exemplifies the first alternative. If successful, the foreign agent 2 entity will use the received X.509 certificate 154d for decrypting the authenticator in the mobile IP 27 registration request 93 and establish a security parameter index (SPI) with a predetermined value designated to public key usage.

In a similar way, the other mobile IP 27 entities may establish security associations with each other using the certificates of the mobile node 154a, foreign agent 154b and home agent 154c as received in the registration request and reply messages respectively.

In order to limit the requirements on revocation check in the mobile node 3, the home agent 1 may perform the revocation list verification of the foreign agent 2 certificate on behalf of the mobile node 3. If successful, the home agent 1 signs the foreign agent 2 certificate and adds it to the registration reply message. Now the mobile node 3 merely has to hold a valid home agent 1 certificate in order validate

For the payload 152, the Internet key exchange (IKE) 80 protocol may utilize the same certificates 154 to establish IPSec security associations. IKE 80 packet 5 will include the initiating parties certificate 154, while packet 9 will include the responding parties certificate 154.

Lastly, it should be noted that the architecture described in this invention, having IPSec run on top of the mobile IP tunnel 30, makes it easy to replace IPSec and IKE 80 with the Transport Layer Security Protocol (TLS) if so requested. This is exemplified in fig. 15d, where the foreign agent 2 and home agent 3 act as TLS application proxies when the mobile node 3 is accessing correspondent nodes 4 on the visited 8 and home 9 network respectively. Such a scenario may have several advantages for an IT-administrator. Foremost it will relieve the mobile node 3 to establish security associations with every correspondent node 4 and vice versa. Furthermore, it off-loads heavy encryption tasks from the correspondent node 4 to an agent 2 or 3, which more likely have encryption implemented in hardware. Finally, by performing encryption on the application layer rather than the IP layer opens up the possibility to apply differentiated services based on transport protocol and port number within the home network 9, visited network 8 and the Internet 6 respectively.